

Socket outlet 2-position; with EURO2 adapter; with plug-in units; without input wiring

Powering Business Worldwide[™]

Part no. S2-KLV Article no. 178971

Similar to illustration

	INOR	, nro	gram
UG	IIVEIV	/ UI U	ıuıaııı

Product image	
Basic function	Accessory consideration
Accessories	KLV
Product range	KLV media DBO

-						
Model With built-in USB power supply Number of units Number of modules (module system) Number of socket outlets switchable Cover Imprint/indication Connection type With hinged lid	Domestic switching devices (EG000013) / Socket outlet (EC000125)					
With built-in USB power supply Number of units Number of modules (module system) Number of socket outlets switchable Cover Imprint/indication Connection type With hinged lid	Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Plug socket (ecl@ss8.1-27-14-40-42 [AKE352011])					
Number of units Number of modules (module system) Number of socket outlets switchable Cover Imprint/indication Connection type With hinged lid	Protective contact (SCHUKO)					
Number of modules (module system) Number of socket outlets switchable Cover Imprint/indication Connection type With hinged lid	No					
Number of socket outlets switchable Cover Imprint/indication Connection type With hinged lid	2					
Cover Imprint/indication Connection type With hinged lid	2					
Imprint/indication Connection type With hinged lid	2					
Connection type With hinged lid	Complete housing					
With hinged lid	Without imprint					
	Plug clamp					
With child-protection	No					
	Yes					
Label space/information surface	No					
Colour	White					
RAL-number (akin)	9010					
Transparent	No					
Lockable	No					
Eject-mechanism	No					
Insulated mounting	Yes					
With function lighting	No					
With orientation lighting	No					
Over voltage protection	No					
Fault current protection	No					
With miniature fuse	No					
Special power supply	-					
Mounting method	-					
Type of fastening	Mounting with screw					
Material	Plastic					
Material quality	Thermoplastic					
Halogen free	Yes					
Surface protection	-					
Type of surface	Not applicable					
With on/off switch	No					
With loop through function	V					
Rotated central insert	Yes					

Nominal current	А		16
Nominal voltage	V		230
Frequency	Hz	z	50 - 50
Rated fault current	m.	ıΑ	0
Phase pickup			None
Suitable for degree of protection (IP)			IP00
For heavy conditions (in accordance with VDE)			No
Impact strength			-
Width of device	m	ım	104
Height of device	m	ım	48
Depth of device	m	ım	65

Additional product information (links)

Product overview (Web) http://www.eaton.eu/DE/Europe/Electrical/ProductsServices/Residential/index.htm