



Fuse-holder, LV, 32 A, AC 550 V, BS88/F1, 1P, BS, front connected, white

Article no. SC32H-DWH
Catalog No. SC32H/DWH

Delivery program

| | | | |
|------------------------------|---|---|--------------------------|
| Product range | | | Fuse accessory |
| Basic function | | | Fuse-holder |
| Field of application | | | low voltage |
| Rated current | I | A | 32 |
| Rated voltage | | | AC 550 V |
| Construction size | | | BS88/F1 |
| Description | | | front connected white |
| Number of poles | | | 1P |
| usable for size/applications | | | fuse-link NSD |
| Standard/Approval | | | BS |
| Standards/Regulations | | | BS88-2 |

Technical data ETIM 6.0

| | | | |
|---|--|---|----|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse base (EC000067) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low-Voltage HRC fuse base (ecl@ss8.1-27-14-21-06 [AKE278010]) | | | |
| Construction size | | | - |
| Number of poles | | | 1 |
| Nominal rated current | | A | 32 |
| Bus-mounting type | | | No |
| Swivelling mechanism | | | No |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusmann.com/pdf/b182a1af-2fc2-4c95-86e9-83297d55051f.pdf |
|-------------------------|---|