



Switch disconnecter, low voltage, 160 A, AC 690 V, NH000, AC21B, 3P, IEC



Powering Business Worldwide™

Article no. EBH00003TS5L
Catalog No. EBH00003TS5L

Delivery program

Product range			Fuse accessory
Basic function			Switch disconnecter
Field of application			low voltage
Rated current	I	A	160
Rated voltage			AC 690 V
Construction size			NH000
Utilization category			AC21B
Description			mounting plate type S-bridge clamps lengthened terminal shrouds
Protection			IP20
Number of poles			3P
usable for size/applications			NH000 fuse-links
Standard/Approval			IEC
Shape			Horizontal
Standards/Regulations			IEC 60947-1 IEC 60947-3

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss8.1-27-37-14-01 [AKF058010])			
Version as main switch			No
Version as safety switch			No
Max. rated operation voltage U _e AC		V	690
Rated permanent current I _u		A	160
Rated operation power at AC-23, 400 V		kW	64
Conditioned rated short-circuit current I _q		kA	100
Rated short-time withstand current I _{cw}		kA	100
Suitable for fuses			NH000
Number of poles			3
With error protection			No
Type of electrical connection of main circuit			Cable clamp
Suitable for ground mounting			No
Suitable for front mounting 4-hole			Yes
Suitable for busbar mounting			No
Type of control element			Cover grip
Position control element			Front side
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			IP30