



Fuse rail, low voltage, 160 A, AC 690 V, NH00, 3P, IEC



Powering Business Worldwide™

Article no. EBF00230S8
Catalog No. EBF00230S8

Delivery program

Product range			Fuse accessory
Basic function			Fuse rail
Field of application			low voltage
Rated current	I	A	160
Rated voltage			AC 690 V
Construction size			NH00
Description			100 mm busbar mounting S-bridge clamps M8 screws
Protection			IP00
Number of poles			3P
usable for size/applications			NH00 fuse-links
Standard/Approval			IEC
Shape			vertical
Standards/Regulations			IEC 60269-1

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / In-line fuse base (EC001046)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse strip (ecl@ss8.1-27-37-14-02 [AKF059010])			
Model			Fuse base
Double interrupting			No
Rated permanent current I _u		A	160
Distance between rail centre, 40 mm			No
Distance between rail centre, 50 mm			No
Distance between rail centre, 60 mm			No
Distance between rail centre, 100 mm			Yes
Distance between rail centre, 185 mm			No
Max. rated operation voltage U _e AC		V	690
Conditioned rated short-circuit current I _q		kA	100
Type of electrical connection of main circuit			-
Number of poles			3
Construction size fuse insert			NH00