



Switch disconnecter, low voltage, 630 A, AC 690 V, NH3, AC21B, 3P, IEC



Powering Business Worldwide™

Article no. **EBV333TW0**
 Catalog No. **EBV333TW0**

Delivery program

Product range			Fuse accessory
Basic function			Switch disconnecter
Field of application			low voltage
Rated current	I	A	630
Rated voltage			AC 690 V
Construction size			NH3
Utilization category			AC21B
Description			185 mm busbar mounting 3-phase simultaneous switching double V-terminals without V-clamps
Protection			IP30
Number of poles			3P
usable for size/applications			NH3 fuse-links
Standard/Approval			IEC
Shape			vertical
Standards/Regulations			IEC 60947-1 IEC 60947-3

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / In-line fuse base (EC001046)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse strip (ecl@ss8.1-27-37-14-02 [AKF059010])			
Model			Fuse switch disconnecter
Double interrupting			No
Rated permanent current I _u		A	630
Distance between rail centre, 40 mm			No
Distance between rail centre, 50 mm			No
Distance between rail centre, 60 mm			No
Distance between rail centre, 100 mm			No
Distance between rail centre, 185 mm			Yes
Max. rated operation voltage U _e AC		V	690
Conditioned rated short-circuit current I _q		kA	80
Type of electrical connection of main circuit			-
Number of poles			3
Construction size fuse insert			NH3