



Phase busbar, 2-phase+HS, 25qmm, pin, 1m



Powering Business Worldwide™

Part no. Z-BB/UL25/2P1MU+AUX/46
Article no. 171138
Catalog No. PDC-TBD7131

Delivery program

Basic function			Busbar
Basic function accessories			Busbar for miniature circuit-breaker
Application			Switchgear for industrial and advanced commercial applications
Busbar type			2-phase + auxiliary contact
Product range			Z-BB/UL

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	100
			0

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])			
Number of phases			2
Number of poles			2
Suitable for number of devices			0
Pitch dimensions		mm	26.4
Cross section		mm ²	25
Length		mm	1000
Number of modular spacings			1
Rated permanent current I _u		A	100
Type of electric connection			Pin
Insulated			Yes
Rated surge voltage		kV	10
Conditioned rated short-circuit current I _q		kA	0
Max. rated operation voltage U _e		V	600
Rated short-time withstand current I _{cw}		kA	0
Suitable for devices with N-busbar			No
Suitable for devices with auxiliary switch			Yes