



Screen winding, for STZ transformer up to 1.6KVA

Part no. +W1,8
Article no. 082270
Catalog No. -

Delivery program

Product range		Accessories
Accessories		Shielding winding IP23 enclosures Inrush current limiters
For use with		STZ0.06 ... STZ1.6
Cu factor 0,00		

Technical data

General

Ambient temperature		-25 - 40
---------------------	--	----------

Characteristics

Insulation class		B/F
Separate windings		●
Rated duty factor	% DF	100

Electrical characteristics

Note		The following applies for the no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values: all details relate to a temperature of 20 °C
------	--	---

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	40

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Component for low-voltage switch technology (accessories) (ecl@ss8.1-27-37-92-01 [AKN570010])		
Type of accessory		-

Approvals

North America Certification		UL/CSA certification not required
-----------------------------	--	-----------------------------------