

Base for pull cord switch, N.O. or N.C, 10A, 250V

Powering Business Worldwide*

Part no. 170-73005/SOCLE-PUSH-BUTTON-NO/NC Article no. 127054

Technical data ETIM 5.0

| Domestic switching devices (EG000013) / Push button (EC000029) | | | |
|--|---|----|-------------------------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Pushbutton (ecl@ss8-27-14-40-44 [AKE354009]) | | | |
| Assembly arrangement | | | Basic element |
| Model | | | Single push button |
| Method of operation | | | Rocker |
| Contacts | | | - |
| Feedback-signal contact | | | No |
| Number of rockers | | | 1 |
| With lighting | | | No |
| Mounting method | | | Flush mounted (plaster) |
| Type of fastening | | | Mounting with claw |
| Material | | | Metal |
| Material quality | | | - |
| Halogen free | | | No |
| Surface treatment | | | Untreated |
| Type of surface | | | Not applicable |
| Colour | | | - |
| RAL-number (akin) | | | 0 |
| Transparent | | | No |
| Label space/information surface | | | No |
| Imprint | | | None |
| Suitable for degree of protection (IP) | | | IP21 |
| Nominal voltage | V | 1 | 250 |
| Rated current | А | ١ | 10 |
| Width of device | m | nm | 71 |
| Height of device | m | nm | 71 |
| Depth of device | m | nm | 42 |
| | | | |