



Semiconductor fuse, superfast, 350A

Part no. 20.610.32-350
Article no. 221161
Catalog No. Z-20-610-32-350

Delivery program

Product range			Accessories
Accessories			Fuses
Rated device current		A	350
Maximum power loss	P _V	W	61
Inside micrometer		mm	80
For use with			DS6-340-75K-MX DS7-34...SX135N0-.... DM4-340-55K DM4-340-75K
For use with			Soft starters

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss8.1-27-14-20-05 [AFZ800012])			
Construction size			NH1
Nominal rated current		A	350
Nominal rated voltage		V	690
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator

Approvals

Product Standards			UL 248-13 CE marking
UL File No.			E180276
UL Category Control No.			JFHR2
CSA File No.			UL report applies to both US and Canada
CSA Class No.			JFHR8
North America Certification			UL recognized, certified by UL for use in Canada
Specially designed for North America			No
Max. Voltage Rating			660V

Dimensions

