




LED, BA 9s green, 12-30VAC/DC, 15mA

**Part no.** A22-LED-G  
**Article no.** 261363  
**Catalog No.** A22-LED-G0

## Delivery program

Product range			Accessories
Accessories			General accessories
Basic function accessories			Single chip LED
Single unit/Complete unit			Single unit
			For AC and DC voltage (positive pole connected to X1) protected against polarity reversal integral circuit-breaker up to 1500 V
Type			12 - 30 V AC/DC/15 mA
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	$t_{\text{mean}}$ (AC)	h	100000
<b>Colour</b>			Green
			
Connection to SmartWire-DT			no

## Technical data

### General

Ambient temperature			
Open		°C	-25 - +70
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	0.75 - 2.5
Stranded		mm <sup>2</sup>	0.5 - 2.5

### Contacts

Rated impulse withstand voltage	$U_{\text{imp}}$	V AC	6000
Rated insulation voltage	$U_i$	V	500
Overvoltage category/pollution degree			III/3

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

## Technical data ETIM 4.0

Colour			Green
Socket			BA9s
Nominal voltage		V	30
Voltage type			AC/DC
Nominal current		mA	15
Diameter		mm	0
Length		mm	0

## Additional product information (links)

<b>IL04716002Z (AWA1160-1745) RMQ-Titan System</b>	
IL04716002Z (AWA1160-1745) RMQ-Titan System	<a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716002Z2016_09.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716002Z2016_09.pdf</a>