




LED, BA 9s, red, 12-30VAC/DC, 15mA

Part no. A22-LED-R
Article no. 261364
Catalog No. A22-LED-RQ

Delivery program

Product range			Accessories
Accessories			General accessories
Basic function accessories			Single chip LED
Single unit/Complete unit			Single unit
			For AC and DC voltage (positive pole connected to X1) protected against polarity reversal integral circuit-breaker up to 1500 V
Type			12 - 30 V AC/DC/15 mA
Lifespan to EN 60064 at $t_a = +25$ °C	t_{mean} (AC)	h	100000
Colour			Red
			
Connection to SmartWire-DT			no

Technical data

General

Ambient temperature			
Open		°C	-25 - +70
Terminal capacities		mm ²	
Solid		mm ²	0.75 - 2.5
Stranded		mm ²	0.5 - 2.5

Contacts

Rated impulse withstand voltage	U_{imp}	V AC	6000
Rated insulation voltage	U_i	V	500
Overvoltage category/pollution degree			III/3

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 4.0

Colour			Red
Socket			BA9s
Nominal voltage		V	30
Voltage type			AC/DC
Nominal current		mA	15
Diameter		mm	0
Length		mm	0

Additional product information (links)

IL04716002Z (AWA1160-1745) RMQ-Titan System

IL04716002Z (AWA1160-1745) RMQ-Titan System ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716002Z2016_09.pdf