





Profile terminal 51x20-42


Part no. **AKP1000**
Article no. **107199**

Delivery program


| | | | |
|---------------------------|-------|----|---|
| Product range | | | 60 mm system 185 mm system |
| Subrange | | | Profile terminals |
| Description | | | Termination to busbars without drilling Put a spacer between the laminated copper busbars when connecting in parallel |
| Width | | mm | 94 |
| Rated operational current | I_e | A | 1600 |
| Copper strip | | mm | 1000 mm ² , terminal area 51 x 20 - 42  |
| Cu factor | | kg | 0,23 |
| For use with | | | Double T profile |

Notes

 round conductor, solid


 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Section conductor, solid

Sector conductor, stranded

 CU band

 CU busbar

Approvals

| | | | |
|--------------------------------------|--|--|---|
| Product Standards | | | UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking |
| UL File No. | | | E307559 |
| UL Category Control No. | | | NMTR2, NMTR8 |
| CSA File No. | | | 236217 |
| CSA Class No. | | | 3211-37 |
| North America Certification | | | UL recognized, CSA certified |
| Conditions of Acceptability | | | Refer to approbation report |
| Specially designed for North America | | | No |
| Suitable for | | | Feeder circuits |
| Current Limiting Circuit-Breaker | | | Refer to approbation report |
| Max. Voltage Rating | | | 600 V AC |
| Degree of Protection | | | Feeder circuits |

Dimensions

