



**Clamp terminal 150-300mm<sup>2</sup>, for 20x5-30x10**

**Part no. AKS300**  
**Article no. 107196**

## Delivery program

Product range			60 mm system 185 mm system
Basic function			Connections
Subrange			Clamp terminals
Description			Termination to busbars without drilling A cable block is used to connect the conductor to the busbar
Width		mm	41
Rated operational current	I <sub>e</sub>	A	600
Copper strip		mm	150 - 300 mm <sup>2</sup> MCM300 - MCM 600. directly terminated,  
Cu factor		kg	0,00
For use with			20 x 5/10 25 x 5/10 30 x 5/10
For use with			Double T profile
<b>Notes</b>			
○ round conductor, solid			
Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
Sector conductor, solid			
Sector conductor, stranded			
CU band			
CU busbar			

## Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

## Dimensions

