

## Metal door, for HxW=2060x600mm, left, white

Part no. BPZ-DS-600/20-L-W Article no. 106421



**Delivery program** 

Basic function Product function Accessories Doors Single unit/Complete unit Description Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock Material Surface finish Unformation about equipment supplied Can be used as right door for two-leaf versions order together with standard door for 600 mm Protection type Suitable for width  Floor-standing enclosures Accessories Accessories Doors Modular system Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock With powder coating can be used as right door for two-leaf versions order together with standard door for 600 mm IP30 Suitable for width	1   - 3   ·	
Product function  Accessories  Doors  Single unit/Complete unit  Description  Description  Material  Surface finish  Information about equipment supplied  Protection type  Suitable for width  Suitable for height  Accessories  Doors  Modular system  Closed Two doors Modunting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock  Sheet steel  With powder coating  can be used as right door for two-leaf versions order together with standard door for 600 mm  1200  Suitable for height  Suitable for height	Product range	Service distribution board IVS
Accessories  Single unit/Complete unit  Description  Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock  Material  Sheet steel  Surface finish  With powder coating  Information about equipment supplied  Can be used as right door for two-leaf versions order together with standard door for 600 mm  Protection type  Suitable for width  Suitable for height  Doors  Modular system  Modular system  Closed  Two doors  Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock  With powder coating  can be used as right door for two-leaf versions order together with standard door for 600 mm  Protection type  Suitable for height  2006	Basic function	Floor-standing enclosures
Single unit/Complete unit  Description  Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock  Material  Surface finish  With powder coating Information about equipment supplied  can be used as right door for two-leaf versions order together with standard door for 600 mm  Protection type  IP30  Suitable for width  Suitable for height  2060	Product function	Accessories
Description  Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock  Material  Sheet steel  Surface finish  Information about equipment supplied  can be used as right door for two-leaf versions order together with standard door for 600 mm  Protection type  IP30  Suitable for width  1200  Suitable for height  Closed Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock  Sheet steel  With powder coating  can be used as right door for two-leaf versions order together with standard door for 600 mm  1200	Accessories	Doors
Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167° 3-point turn lock with roller lever lock  Material  Sheet steel  Surface finish  With powder coating  Information about equipment supplied  can be used as right door for two-leaf versions order together with standard door for 600 mm  Protection type  IP30  Suitable for width  2060	Single unit/Complete unit	Modular system
Surface finish  Information about equipment supplied  Protection type  Suitable for height  With powder coating  can be used as right door for two-leaf versions order together with standard door for 600 mm  IP30  Suitable for height  2060	Description	Two doors Mounting from front, fast mounting, hinges on left or right possible Door opening angle 167°
Information about equipment supplied  can be used as right door for two-leaf versions order together with standard door for 600 mm  Protection type  IP30  Suitable for width  1200  Suitable for height  2060	Material	Sheet steel
order together with standard door for 600 mm  Protection type  Suitable for width  1200  Suitable for height  2060	Surface finish	With powder coating
Suitable for height 1200  2060	Information about equipment supplied	
Suitable for height 2060	Protection type	IP30
	Suitable for width	1200
Protective cover mounted on left	Suitable for height	2060
		Protective cover mounted on left

## Notes

Two-section doors are used from width 1000 mm, order the right and left doors separately.