

## Connection cable, 3p, AC, coupling m12 angled, open end, L=2m



Part no. CSAR3F3CY2202 Article no. 136262

Catalog No. CSAR3F3CY2202

**Delivery program** 

Basic function		Accessories
Accessories		Connecting cables
Length	mm	2000
Pin assignment		2 3 1 = Green 2 = Red/Black 3 = Red/White
Voltage type		AC
Number of poles		3 pole
Style output side		Cable end, open
Style input side		Coupling, angled
For use with		
For use with		AC sensors, 3 pole, M12

## **Design verification as per IEC/EN 61439**

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

## **Technical data ETIM 6.0**

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecl@ss8.1-27-27-92-18 [ACN870008])

(accessories)/ Sensor-actuator patch cord (sensor technology acc.) (eci@sso.1-27	1-21-32-10 [AUIV	10/0000])	
Number of poles			3
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Angled
Type of electrical connection, box-sided			-
Type of plug-in contact, box-sided			-
Positioning cable feed, box-sided			-
Cable length		m	2
Material of cable sheath			-
Halogen free			No
Colour cable sheath			-
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			•
Material of contact surface			
Permitted cable outer temperature, fixed		°C	-40 - 70
Permitted cable outer temperature, in movement		°C	-40 - 70
Rated current In		Α	0
Nominal rated voltage		V	0
Continuity resistor		m0hm	0

## **Approvals**

Product Standards	CE marking	