




Connection cable, 4p, AC, coupling M12 flat, open end, L=10m

Part no. CSAS4A4CY2210
Article no. 136312
Catalog No. CSAS4A4CY2210

Delivery program

Basic function			Accessories
Accessories			Connecting cables
Length		mm	10000
Pin assignment			 <p>1 = Brown 2 = Blue 3 = Black 4 = White</p>
Voltage type			AC
Number of poles			4 pole
Style output side			Cable end, open
Style input side			Coupling, straight
For use with			
For use with			AC sensors, 4 pole, M12

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecI@ss8.1-27-27-92-18 [ACN870008])			
Number of poles			4
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			-
Type of plug-in contact, box-sided			-
Positioning cable feed, box-sided			-
Cable length		m	10
Material of cable sheath			-
Halogen free			No
Colour cable sheath			-
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			-
Material of contact surface			-
Permitted cable outer temperature, fixed		°C	-40 - 70
Permitted cable outer temperature, in movement		°C	-40 - 70
Rated current In		A	0
Nominal rated voltage		V	0
Continuity resistor		mOhm	0

Approvals

Product Standards			CE marking
-------------------	--	--	------------