




Connection cable, 4p/3Ltg, DC current, coupling m12 angled, open end, L=5m



Powering Business Worldwide™

Part no. CSDR4A3CY2205-LN
 Article no. 136274
 Catalog No. CSDR4A3CY2205-LN

Delivery program

Basic function			Accessories
Accessories			Connecting cables
Length		mm	5000
Pin assignment			 <ul style="list-style-type: none"> 1 = Brown 2 = White 3 = Blue 4 = Black
Voltage type			DC
Number of poles			4-pole, 3-conductor
Style output side			Cable end, open
Style input side			Coupling, angled
For use with			
For use with			DC sensors, 4 pole, 2 or 3- wire connection, M12

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecI@ss8.1-27-27-92-18 [ACN870008])			
Number of poles			4
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Angled
Type of electrical connection, box-sided			-
Type of plug-in contact, box-sided			-
Positioning cable feed, box-sided			-
Cable length		m	5
Material of cable sheath			-
Halogen free			No
Colour cable sheath			-
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			-
Material of contact surface			-
Permitted cable outer temperature, fixed		°C	-40 - 70
Permitted cable outer temperature, in movement		°C	-40 - 70
Rated current In		A	0
Nominal rated voltage		V	0
Continuity resistor		mOhm	0

Approvals

Product Standards			CE marking
-------------------	--	--	------------

