



Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=1.5m



Powering Business Worldwide™

Part no. CSDR4A4CY2201.5-D
Article no. 136313
Catalog No. CSDR4A4CY2201P5-D

Delivery program

Basic function			Accessories
Accessories			Connecting cables
Length		mm	1500
Pin assignment			<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Face view female</p> </div> <div style="text-align: center;"> <p>Face view male</p> </div> </div>
Voltage type			DC
Number of poles			4 pole
Style output side			Plug, angled
Style input side			Coupling, straight
For use with			
For use with			DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecl@ss8.1-27-27-92-18 [ACN870008])			
Number of poles			4
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			M12
Type of plug-in contact, box-sided			Male (plug)
Positioning cable feed, box-sided			Angled
Cable length		m	1.5
Material of cable sheath			-
Halogen free			No
Colour cable sheath			-
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			-
Material of contact surface			-
Permitted cable outer temperature, fixed		°C	-40 - 70
Permitted cable outer temperature, in movement		°C	-40 - 70
Rated current In		A	0
Nominal rated voltage		V	0
Continuity resistor		mOhm	0

Approvals

Product Standards			CE marking
-------------------	--	--	------------

