



Connection cable, 4p, DC current, coupling M12 flat, plug, angled, L=5m

Part no. CSDR4A4CY2205-D
Article no. 136283
Catalog No. CSDR4A4CY2205-D

Delivery program

Basic function		Accessories
Accessories		Connecting cables
Length	mm	5000
Pin assignment		
Voltage type		DC
Number of poles		4 pole
Style output side		Plug, angled
Style input side		Coupling, straight
For use with		
For use with		DC sensors, 4 pole, 2, 3 or 4-wire connection, M12

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 6.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)		
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecl@ss8.1-27-27-92-18 [ACN870008])		
Number of poles		4
Type of electrical connection, field-sided		M12
Type of plug-in contact, field sided		Female (bus)
Positioning cable feed, field-sided		Straight
Type of electrical connection, box-sided		M12
Type of plug-in contact, box-sided		Male (plug)
Positioning cable feed, box-sided		Angled
Cable length	m	5
Material of cable sheath		-
Halogen free		No
Colour cable sheath		-
With LED indication		No
Screened		No
Type of cable		Multi-core
Vulcanize		No
Material contact body		-
Material of contact surface		-
Permitted cable outer temperature, fixed	°C	-40 - 70
Permitted cable outer temperature, in movement	°C	-40 - 70
Rated current In	A	0
Nominal rated voltage	V	0
Continuity resistor	mOhm	0

Approvals

Product Standards		CE marking
-------------------	--	------------

