



Connection cable, 5p/5Ltg, DC current, coupling m12 angled, open end, 2m



Powering Business Worldwide™

Part no. CSDR5A5CY2202  
 Article no. 166983  
 Catalog No. CSDR5A5CY2202

## Delivery program

Basic function			Accessories
Accessories			Connecting cables
Length		mm	2000
Pin assignment			 <ul style="list-style-type: none"> <li>1 = Brown</li> <li>2 = White</li> <li>3 = Blue</li> <li>4 = Black</li> <li>5 = Green/Yellow</li> </ul>
Voltage type			DC
Number of poles			5 pole
Style output side			Cable end, open
Style input side			Coupling, angled
<b>For use with</b>			
For use with			DC sensors, IntelliView E75-DST4..., 5 pole, M12

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

## Technical data ETIM 6.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecI@ss8.1-27-27-92-18 [ACN870008])			
Number of poles			0
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Angled
Type of electrical connection, box-sided			-
Type of plug-in contact, box-sided			-
Positioning cable feed, box-sided			-
Cable length		m	2
Material of cable sheath			-
Halogen free			No
Colour cable sheath			-
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			-
Material of contact surface			-
Permitted cable outer temperature, fixed		°C	-40 - 70
Permitted cable outer temperature, in movement		°C	-40 - 70
Rated current I <sub>n</sub>		A	0
Nominal rated voltage		V	0
Continuity resistor		mOhm	0