



Connection cable, 4p, DC current, coupling M12 flat, plug, straight, L=1m



Powering Business Worldwide™

Part no. CSDS4A4CY2201-D  
 Article no. 136291  
 Catalog No. CSDS4A4CY2201-D

## Delivery program

|                     |  |    |  |
|---------------------|--|----|--|
| Basic function      |  |    | Accessories  |
| Accessories         |  |    | Connecting cables                                  |
| Length              |  | mm | 1000   |
| Pin assignment      |  |    |  |
| Voltage type        |  |    | DC   |
| Number of poles     |  |    | 4 pole   |
| Style output side   |  |    | Plug, straight                                     |
| Style input side    |  |    | Coupling, straight                                 |
| <b>For use with</b> |  |    |  |
| For use with        |  |    | DC sensors, 4 pole, 2, 3 or 4-wire connection, M12 |

## Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |

## Technical data ETIM 6.0

|   |  |      |              |
|---|--|------|--------------|
| Sensors (EG000026) / Sensor-actuator patch cord (EC001855)  |  |      |              |
| Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecl@ss8.1-27-27-92-18 [ACN870008]) |  |      |              |
| Number of poles   |  |      | 4            |
| Type of electrical connection, field-sided  |  |      | M12          |
| Type of plug-in contact, field sided  |  |      | Female (bus) |
| Positioning cable feed, field-sided   |  |      | Straight     |
| Type of electrical connection, box-sided  |  |      | M12          |
| Type of plug-in contact, box-sided  |  |      | Male (plug)  |
| Positioning cable feed, box-sided   |  |      | Straight     |
| Cable length  |  | m    | 1            |
| Material of cable sheath  |  |      | -            |
| Halogen free  |  |      | No           |
| Colour cable sheath   |  |      | -            |
| With LED indication   |  |      | No           |
| Screened  |  |      | No           |
| Type of cable   |  |      | Multi-core   |
| Vulcanize   |  |      | No           |
| Material contact body   |  |      | -            |
| Material of contact surface   |  |      | -            |
| Permitted cable outer temperature, fixed  |  | °C   | -40 - 70     |
| Permitted cable outer temperature, in movement  |  | °C   | -40 - 70     |
| Rated current In  |  | A    | 0            |
| Nominal rated voltage   |  | V    | 0            |
| Continuity resistor   |  | mOhm | 0            |

## Approvals

|                   |  |  |            |
|-------------------|--|--|------------|
| Product Standards |  |  | CE marking |
|-------------------|--|--|------------|

