




8-pin/8-conductor connecting cable, DC, flat/open, 10



Powering Business Worldwide™

Part no. CSDS8A8CB2410
Article no. 100580
Catalog No. CSDS8A8CB2410

Delivery program

Basic function			Accessories
Accessories			Connecting cables
Pin assignment			
Voltage type			DC
Number of poles			8 pole
Style output side			Cable end, open
Style input side			Coupling, straight
For use with			
For use with			DC sensors, IntelliView E76-CLR..., 8 pole, M12

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Binary sensor technology, safety-related sensor technology (accessories) / Sensor-actuator patch cord (sensor technology acc.) (ecl@ss8.1-27-27-92-18 [ACN870008])			
Number of poles			8
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Straight
Type of electrical connection, box-sided			-
Type of plug-in contact, box-sided			-
Positioning cable feed, box-sided			-
Cable length		m	10
Material of cable sheath			-
Halogen free			No
Colour cable sheath			Black
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			-
Material of contact surface			-
Permitted cable outer temperature, fixed		°C	-40 - 70
Permitted cable outer temperature, in movement		°C	-40 - 70
Rated current In		A	0
Nominal rated voltage		V	0
Continuity resistor		mOhm	0