



Proximity Sensor, M30, analog, $S_n=1-12\text{mm}$, 15-30VDC, 0-20mA, 0-10V, line
2m



Powering Business Worldwide™

Part no. E59-A30A112C02-CV
Article no. 166719
Catalog No. E59-A30A112C02-CV

Delivery program

Basic function			Inductive Sensors
Product range			E59 AccuProx Series
Description			Current output (0 - 20 mA) and voltage output (0 - 10 V)
Connection			3-wire/4-wire
Design (outer dimensions)		mm	M30 x 1.5
Rated operational voltage	U_e		15 - 30 V DC
Rated switching distance	S_n	mm	1 - 12
Type of mounting			Flush
Switching type			Analog
For connection of:			2 m connection cable
Material			Stainless steel
Degree of Protection			IP67

Technical data

General

Standards			IEC/EN 60947-5-2
Ambient temperature			-40 - +70
Mechanical shock resistance		g	30 Shock duration 11 ms
Degree of Protection			IP67

Characteristics

Repetition accuracy of S_n		%	1
Temperature drift of S_n		%	10
Rated operational voltage	U_e		15 - 30 V DC
Switching state display		LED	Red
Operating voltage display		LED	Green
Connection			3-wire/4-wire
Style			
Design (outer dimensions)		mm	M30 x 1.5
For connection of:			2 m connection cable
Material			Stainless steel

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-40
Operating ambient temperature max.		°C	70

Approvals

Product Standards			UL 508; CSA-C22.2 No. 14; IEC60947-5-2; CE marking
UL File No.			E166051
UL Category Control No.			NRKH, NRKH7
CSA File No.			50513
CSA Class No.			3211-03
North America Certification			UL listed, CSA certified
Max. Voltage Rating			30 V DC
Degree of Protection			IEC: IP67; UL/CSA Type: 4, 4x, 6, 6P, 12, 13

Additional product information (links)

IL05301010Z AccuProx Series Analog Inductive Sensors

IL05301010Z AccuProx Series Analog Inductive Sensors ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL05301010Z2016_07.pdf