

EV busbars 2Ph., 7HP, for auxiliary contact unit

Powering Business Worldwide*

Part no. EVG-16/2PHAS/6MODUL/HI Article no. 291483

Similar to illustration

Delivery program

71 0		
Basic function	Busbar	
Basic function accessories	Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker	
Busbar type	2-phase + auxiliary contact	
Product range	EVG	

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])

Number of phases		2
Number of poles		2
Suitable for number of devices		3
Pitch dimensions	mm	0
Cross section	mm²	16
Length	mm	267
Number of modular spacings		6
Rated permanent current lu	Α	80
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current Iq	kA	25
Max. rated operation voltage Ue	V	415
Rated short-time withstand current lcw	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		Yes

Dimensions

