



EV busbars 4Ph., 8HP, 80A for PLS. CLS. PKN., PFIM, PFHM, PFNM

Part no. EVG-16/4PHAS/8MODUL
Article no. 291475

Similar to illustration

Delivery program

Basic function			Busbar
Basic function accessories			Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker
Busbar type			4-phase
Product range			EVG

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])			
Number of phases			4
Number of poles			4
Suitable for number of devices			2
Pitch dimensions		mm	0
Cross section		mm ²	16
Length		mm	142.4
Number of modular spacings			8
Rated permanent current I _u		A	80
Type of electric connection			Fork
Insulated			Yes
Rated surge voltage		kV	4
Conditioned rated short-circuit current I _q		kA	25
Max. rated operation voltage U _e		V	415
Rated short-time withstand current I _{cw}		kA	0
Suitable for devices with N-busbar			No
Suitable for devices with auxiliary switch			No

Dimensions

