



## EV busbars 3Ph., 10HP

**Part no.** EVG-25/3PHAS/N/10MODUL/LS  
**Article no.** 121093

Similar to illustration

### Technical data ETIM 6.0

|   |  |                 |      |
|---|--|-----------------|------|
| Low-voltage industrial components (EG000017) / Phase busbar (EC000215)  |  |                 |      |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008]) |  |                 |      |
| Number of phases  |  |                 | 3    |
| Number of poles   |  |                 | 3    |
| Suitable for number of devices  |  |                 | 0    |
| Pitch dimensions  |  | mm              | 0    |
| Cross section   |  | mm <sup>2</sup> | 10   |
| Length  |  | mm              | 255  |
| Number of modular spacings  |  |                 | 10   |
| Rated permanent current I <sub>u</sub>  |  | A               | 63   |
| Type of electric connection   |  |                 | Fork |
| Insulated   |  |                 | Yes  |
| Rated surge voltage   |  | kV              | 4    |
| Conditioned rated short-circuit current I <sub>q</sub>  |  | kA              | 25   |
| Max. rated operation voltage U <sub>e</sub>   |  | V               | 415  |
| Rated short-time withstand current I <sub>cw</sub>  |  | kA              | 0    |
| Suitable for devices with N-busbar  |  |                 | Yes  |
| Suitable for devices with auxiliary switch  |  |                 | No   |