

EV busbars 3Ph., 4+5HP, for combined FI-/LS unit with 4 p-FI

Powering Business Worldwide

Part no. EVG-3PHAS/N/5MODUL/LS Article no. 215659

Similar to illustration

Delivery program

Basic function	Busbar
Basic function accessories	Busbar for miniature circuit-breaker Busbar for residual-current circuit-breakers Busbar for combined residual-current/power circuit-breaker
Busbar type	3-phase + auxiliary contact
Product range	EVG

Technical data ETIM 6.0			
Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8.1-27-37-13-06 [ACN992008])			
Number of phases		3	
Number of poles		4	
Suitable for number of devices		0	
Pitch dimensions	mm	0	
Cross section	mm²	10	
Length	mm	157	
Number of modular spacings		5	
Rated permanent current lu	Α	63	
Type of electric connection		Fork	
nsulated		Yes	
Rated surge voltage	kV	4	
Conditioned rated short-circuit current Iq	kA	25	
Max. rated operation voltage Ue	V	500	
Rated short-time withstand current lcw	kA	0	
Suitable for devices with N-busbar		No	
Suitable for devices with auxiliary switch		No	