




Fuse enclosure, 1xdisconnecter 3p NH3 630A, HxWxD=750x375x225mm



Powering Business Worldwide™

Part no. **GSTA3/148**
Article no. **020282**

Delivery program

Dimensions		mm	
Product range			CI insulated enclosures
Basic function			Enclosures with devices fitted
Product function			Distribution board enclosure with NH fuse switch-disconnector
Single unit/Complete unit			Stand-alone device
Degree of Protection			IP65
Description			Sides closed, but with full area knockout Open top and bottom Sealable cover fasteners Fuse switch-disconnector fitted to steel mounting plate Mounting plate protruding 50 mm Terminal for connecting the 4th conductor (PEN)
Type cover			Transparent
Width		mm	375
Height		mm	750
Fuse cartridge		Size	NH3
Rated operational current	I_e	A	500 400
Rated operational voltage	U_e	V AC	500 660 690
consists of			
Basic enclosure			CI48-200
Mounting system			L1-CI44
Base unit		B x H x D	GSTA3
Accessories			HS 50-CI
Notes Stepped cable grommets →#057621 Fuse links →#288934 →#288909 →#100651			

Additional product information (links)

Manufacturer's Declaration CI-RoHS	ftp://ftp.moeller.net/DOCUMENTATION/PDF/2013-01-31_Ci_RoHS.pdf
Declaration of conformity	ftp://ftp.moeller.net/DOCUMENTATION/PDF/ci_ce.pdf