

## Actuating rod aluminum

**Part no.** HH-A  
**Article no.** 063268  
**Catalog No.** HH-A



## Delivery program

|                              |   |    |  |
|------------------------------|---|----|--|
| Basic function               |   |    | Components   |
| Part group reference         |   |    | AT4  |
| Product range                |   |    | Actuators  |
| Function                     |   |    | Actuating rod  |
| Description                  |   |    | For adding R-AT4 rotary drive<br>With adjustable aluminium rod<br>Not to be used as a safety position switch |
| Max. operating speed lateral |   |    | 1.4  |
| Lever length                 | l | mm | 190  |
| For use with                 |   |    | R-AT4  |



## Technical data

### General

|                       |  |                 |  |
|-----------------------|--|-----------------|--|
| Standards             |  |                 | IEC/EN 60947   |
| Climatic proofing     |  |                 | Damp heat, constant, to IEC 60068-2-78; damp heat, cyclical, to IEC 60068-2-30 |
| Mounting position     |  |                 | As required  |
| Terminal capacities   |  | mm <sup>2</sup> |  |
| Solid                 |  | mm <sup>2</sup> | 1 x (0.75 - 2.5)<br>2 x (0.75 - 1.5)   |
| Flexible with ferrule |  | mm <sup>2</sup> | 1 x (0.5 - 1.5)<br>2 x (0.5 - 1.5)   |

### Contacts/switching capacity

|  |           |      |          |
|--|-----------|------|----------|
| Rated impulse withstand voltage          | $U_{imp}$ | V AC | 6000     |
| Rated insulation voltage                 | $U_i$     | V    | 500      |
| Overvoltage category/pollution degree    |           |      | III/3    |
| Rated operational current                | $I_e$     | A    |          |
| AC-15                                    |           |      |          |
| 24 V                                     | $I_e$     | A    | 10       |
| 220 V 230 V 240 V                        | $I_e$     | A    | 6        |
| 380 V 400 V 415 V                        | $I_e$     | A    | 4        |
| DC-13                                    |           |      |          |
| 24 V                                     | $I_e$     | A    | 3        |
| 110 V                                    | $I_e$     | A    | 0.8      |
| 220 V                                    | $I_e$     | A    | 0.4      |
| Supply frequency                         |           | Hz   | max. 400 |
| Short-circuit rating to IEC/EN 60947-5-1 |           |      |          |

|  |              |  |
|--|--------------|--|
| max. fuse  | A gG/gL      | 6  |
| Repetition accuracy  | mm           | 0.02   |
| <b>Mechanical variables</b>                                |              |  |
| Contact temperature of roller head                         | °C           |  100  |
| Mechanical shock resistance (half-sinusoidal shock, 20 ms) |              |  |
| Standard-action contact                                    | g            | 5  |
| Snap-action contact  | g            | 2  |
| Operating frequency  | Operations/h |  6000 |
| <b>Actuation</b>   |              |  |
| Mechanical   |              |  |
| Actuating torque of rotary drives                          | Nm           | 0.3  |

## Design verification as per IEC/EN 61439

|  |            |    |  |
|--|------------|----|--|
| Technical data for design verification   |            |    |  |
| Rated operational current for specified heat dissipation   | $I_n$      | A  | 0  |
| Heat dissipation per pole, current-dependent   | $P_{vid}$  | W  | 0  |
| Equipment heat dissipation, current-dependent  | $P_{vid}$  | W  | 0  |
| Static heat dissipation, non-current-dependent   | $P_{vs}$   | W  | 0  |
| Heat dissipation capacity  | $P_{diss}$ | W  | 0  |
| Operating ambient temperature min.   |            | °C | -25  |
| Operating ambient temperature max.   |            | °C | 70   |
| IEC/EN 61439 design verification   |            |    |  |
| 10.2 Strength of materials and parts   |            |    |  |
| 10.2.2 Corrosion resistance  |            |    | Meets the product standard's requirements.   |
| 10.2.3 Verification of thermal stability of enclosures   |            |    |  |
| 10.2.3.1 Verification of thermal stability of enclosures   |            |    | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |            |    |  |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |            |    | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |            |    |  |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |            |    | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |            |    | Please enquire   |
| 10.2.5 Lifting   |            |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.6 Mechanical impact   |            |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.7 Inscriptions  |            |    | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |            |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.4 Clearances and creepage distances   |            |    | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |            |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.6 Incorporation of switching devices and components   |            |    | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.7 Internal electrical circuits and connections  |            |    | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |            |    | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |            |    |  |
| 10.9.2 Power-frequency electric strength   |            |    | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |            |    | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |            |    | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |            |    | Not applicable.  |
| 10.11 Short-circuit rating   |            |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.12 Electromagnetic compatibility  |            |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function  |            |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 6.0

|   |               |
|---|---------------|
| Sensors (EG000026) / Drive head for position switches/hinge switches (EC001483)   |               |
| Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Position switch / Drive head for position switches (ecl@ss8.1-27-27-06-04 [BAA083009]) |               |
| Type of control element   | Actuating rod |

