

**Part no.** IZM-CAS634-4000  
**Article no.** 122868

### Delivery program

|   |             |   |  |
|---|-------------|---|--|
| Product range                               |             |   | Accessories  |
| Current Range                               |             |   | 4000 to 6300 A   |
| Accessories                                 |             |   | Withdrawable units   |
| Accessories                                 |             |   | Cassettes  |
| Standard/Approval                           |             |   | IEC  |
| Number of poles                             |             |   | 4 pole   |
| Rated current = rated uninterrupted current | $I_n = I_u$ | A | 4000   |
|   |             |   | Standard components fitted to separately ordered cassette: <ul style="list-style-type: none"> <li>• Arc chute cover</li> <li>• Complete set of auxiliary conductors</li> <li>• Coding between cassette and switch</li> <li>• Horizontal Connection</li> <li>• Door seal</li> </ul> |
| Rated current                               | $I_n$       | A | 4000   |
| Pole  |             |   | 4  |
| For use with                                |             |   | IZM63...W<br>IN63...W  |

### Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |
| Operating ambient temperature max.     |  | °C | 70  |