

Cassette 2000A, IZMX403 m. control cable connection

Powering Business Worldwide*

Part no. IZMX-CAS403-2000-SEC Article no. 150085

Catalog No. RESC083WSW0NMNN2MNDX

Delivery program

Product range			Accessories
Accessories			Withdrawable units
Accessories			Cassettes
			Equipment supplied: arcing chamber cover, coding to basic device
Rated current	In	Α	2000
Pole			3
For use with			IZMX403W INX403W
Instructions			With control conductor terminals fully fitted.
Information about equipment supplied			with arcing chamber cover
			Control circuit terminal
Notes			
Including complete set of control terminals			

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss8.1-27-37-04-22 [ACN955008])					
Rated current In	Α	2000			
Number of poles		3			
Version as busbar adapter		No			
Version as built-in device		Yes			
Type of electrical connection of main circuit		Rail connection			