



## Cassette 2500A, IZMX403 without control cable connection

**Part no.** IZMX-CAS403-2500  
**Article no.** 122883

### Delivery program

Accessories			Withdrawable units
Accessories			Cassettes
Rated current	$I_n$	A	2500
Rated ultimate short-circuit breaking capacity	$I_{cu}$	kA	65
Pole			3
For use with			IZMX40...3-...W INX40...3-...W
<b>Instructions</b>			Without terminal blocks for the control circuit terminals. Please order the required quantity separately.
Information about equipment supplied			with arcing chamber cover
<b>Notes</b>			
Without control circuit terminals			

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

### Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ec1@ss8.1-27-37-04-22 [ACN955008])			
Rated current $I_n$		A	2500
Number of poles			3
Version as busbar adapter			No
Version as built-in device			Yes
Type of electrical connection of main circuit			Rail connection