



Cell switch contacts, 2C/0

Part no. IZMX-CS40
Article no. 124287
Catalog No. IZMX-CS40

Delivery program

| | | | |
|---------------------|--|--|------------------------------|
| Product range | | | Accessories |
| Accessories | | | Withdrawable units |
| Accessories | | | Position signalling switches |
| For use with | | | IZMX-CAS40... |
| Instructions | | | For external application |

Technical data

Rated breaking capacity

| | | | |
|----------------|--|---|------|
| Inductive load | | | |
| 250 V AC | | A | 10 |
| 125 V DC | | A | 0.5 |
| 250 V DC | | A | 0.25 |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |

Technical data ETIM 6.0

| | | | |
|---|--|---|-------------------------|
| Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss8.1-27-37-13-02 [AKN342010]) | | | |
| Number of contacts as change-over contact | | | 1 |
| Number of contacts as normally open contact | | | 2 |
| Number of contacts as normally closed contact | | | 2 |
| Rated operation current I _e at AC-15, 230 V | | A | 10 |
| Type of electric connection | | | Flat plug-in connection |
| Model | | | Half-integrated |
| Mounting method | | | Floor fastening |