











**Connection terminal, 630A, 3p, flat/round**

**Part no. K2X240/3**  
**Article no. 046374**

**Delivery program**

Product range			General switchboard accessories
Product function			Accessories panel building
Accessories			Terminations
Accessories			Terminals, 160 – 1000 A
Rated insulation voltage	$U_i$	V AC	1000
Description			Including labels for terminal marking U, V, W - X, Y, Z - L1, L2, L3 - T1, T2, T3 - PE, N, PEN,  Relationship of rated operational current → terminal capacity to IEC/EN 60439, VDE 0660 Part 500 or EN 50021 Outer terminal for round or sectoral conductor, other side for Cu strip
Rated operational current	$I_e$	A	630
Pole			3
<b>Terminal capacity</b>			
Cu/Al cable			
			Cu  Round stranded  Sectoral stranded  Round solid  Sectoral solid Al  Round solid  Sectoral solid
			1 x 150 - 300 2 x 50 - 240
Al cable			
			Al  Sectoral solid
			1 x 150 - 240 2 x 95 - 185
Copper band		mm	10 x 16 x 0.8 11 x 21 x 1
			 copper strip
Copper strip		mm	40 x 15
			 Cu bar
<b>Notes</b> Conversion kits for strip terminal in cable connection available separately Terminal covers available separately			