

Distribution board terminal enclosure, +terminal block, 4p, 630A

Powering Business Worldwide*

Part no. K2X240/4/KST48
Article no. 055880

Delivery program

Delivery program			
Product view			
Dimensions		mm	95 95 95 4 95 4 95 4 95 95 95 95 95 95 95 95 95 95 95 95 95
Product range			Ci insulated enclosures
Basic function			Prepared enclosures
Product function			Distribution board terminal enclosure
Accessories			Distribution board terminal enclosure
Single unit/Complete unit			Complete housing
Width		mm	375
Height		mm	750
Depth		mm	225
Description			Distribution boards with terminals and fitted gland plate External connection for round and sector conductors, internal for Cu band, conversion kits and sector conductors Large area knockouts at top and openings for taking wedge-lock Closed side walls in which large openings can be created by knocking out Mounting of cable connectors in distribution board connection via wedge-lock Stepped cable grommet split gland plate Cables can be inserted from the front KST enclosure with fitted gland plate retrofitting possible with Ci distribution board enclosures and Ci individual enclosures
Degree of Protection			IP65 (gland plates at the bottom)
Rated uninterrupted current	I _u	Α	630
Pole			4
Stranded		mm ²	1 x 150300 2 x 50 x 240 11 x 21 x 1.0
Basic enclosure			KST48-200
Mounting system			L5-C143
Devices		Number	K2x240/ (4 oder 5)

Additional product information (links)

the control of the co	
Manufacturer's Declaration CI-RoHS	ftp://ftp.moeller.net/DOCUMENTATION/PDF/2013-01-31_Ci_RoHS.pdf
Declaration of conformity	ftp://ftp.moeller.net/DOCUMENTATION/PDF/ci_ce.pdf