




PE-terminal 5C., 25A, 1.5-6qmm

Part no. K6/1
Article no. 002270

Delivery program

Product range		CI-B, C, D basic enclosures
Basic function		Basic enclosures
Product function		Accessories for CI-B, C, D basic enclosures
Accessories		PE terminal (5th conductor)
For use with		CI-B CI-C CI-D
For use with		Rated current 25 A for  1.5 - 6 mm ² Solid
Terminal capacity for round conductor	mm ²	<input type="radio"/> 1.5 - 6


Notes

Terminal capacity

- solid
- stranded
- flexible with ferrule

Notes

L



Knockouts
2 x M20

Approvals

North America Certification		UL/CSA certification not required
-----------------------------	--	-----------------------------------

Additional product information (links)

Technical overview cam switch, switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.2
System overview cam switch T	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.4
System overview switch-disconnector P	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.6
Key to part numbers Cam switch	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Key to part numbers Switch-disconnector	http://de.ecat.moeller.net/flip-cat/?edition=HPLTEv1&startpage=4.8
Switches for ATEX	http://www.coopercrouse-hinds.eu/en/products/25-ex-safety-and-main-current-switches.html