



Spare key SA

Part no.

Article no.

Catalog No.

M22-ES-SA(*)-*

217444

-



Powering Business Worldwide™

Delivery program

Product range			Accessories
Basic function accessories			Individual keys
Single unit/Complete unit			Single unit
Degree of Protection			IP66
Connection to SmartWire-DT			no
Note asterisk part number			Please configure the asterisks in the cart
Set of rules			#SM-Stern_RMQ-Titan_Formular_frei
Form			Bestellung erfolgt über Formular MZ047002ZU_DEEN (früher F0276) -> Datasheet in Online catalog
Notes			
Master key systems: Delivery time 4 to 6 weeks after receipt of order			
To order use form F0276 Data sheet in Online Catalog			

Technical data

General

Ambient temperature			
Open		°C	-25 - +70

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Control circuit devices (accessories) (ecl@ss8.1-27-37-92-16 [AC0043008])			
Type of electrical accessory			-
Type of mechanical accessory			Key

Approvals

North America Certification			UL/CSA certification not required
-----------------------------	--	--	-----------------------------------

Additional product information (links)

Form MZ047002ZU (former F0276) for ordering master key systems	ftp://ftp.moeller.net/DOCUMENTATION/PDF/MZ047002ZU_DEEN.pdf
--	---