




Insulated enclosure, HxWxD=250x187.5x175mm, for size 1

Part no. NZM1-XCI23-TVD
Article no. 271522

Delivery program

			
Product range			Accessories
Accessories			Insulated enclosures
Description			With door coupling rotary handle Complete with all required functional parts
Function			Standard, black/grey
Locking facility			Lockable on the 0 position on the handle using up to 3 padlocks. Additionally with cover interlock.
Accessories			Accessories, others
Number of poles			3 pole
Standard/Approval			IEC
Construction size			NZM1
Degree of Protection			IP65
Rated uninterrupted current I_u at max. cross-section	I_u	A	63 A
Basic enclosure			CI23-150
Terminal for retrofitting of 5th conductor (neutral conductor)			K10/1, K25/1
For use with			NZM1, PN1, N(S)1

Notes

Suitable for installation of circuit-breakers and switch-disconnectors Enclosure for separate mounting with top and bottom cable entry.

Include fixing straps for wall mounting.

Short-circuit resistance at 415 V 50/60 Hz to 10 kA.

Cannot be used in combination with NZM...-XR... remote operator...

NZM...-XSV plug-in unit or NZM...-XAV withdrawable unit.

Insulated additional terminal for 4th or 5th pole should be ordered separately.

CI-K5 enclosure with hard metric knock-outs

CI23 enclosure with flanges

CI43, CI45 and CI48 feature gland plates.

Only for switches with tunnel clamps for direct connection of cables.

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ec1@ss8.1-27-37-13-01 [AKN343011])

Material housing			Plastic
Width		mm	187.5
Height		mm	250
Depth		mm	175
With transparent cover			Yes

Suitable for emergency stop		No
Model		Surface mounting
Degree of protection (IP)		IP65

Dimensions

