



Display device, for measuring and communication modules

Part no. NZM-XMC-DISP
Article no. 129967

Delivery program

Product range		Accessories
Accessories		Measuring modules
Accessories		Accessories, diagnostics & communication
Description		Front dimensions 96 x 96 mm Front cutout 92 x 92 mm
Description		For flush mounting on doors (connection to local display) For all measuring and communication modules with a Modbus interface Phase-specific indication of currents, voltages, power, and energy values Pre-configured screens available Cannot be combined with NZM-XMC-TC-MB
For use with		NZM...XMC-MB
Rated operating frequency		DC
Standard/Approval		IEC
Construction size		NZM2/3
Notes		
Connection to NZM...XMC-MB using four-wire data cable (not included as standard).		
Cannot be combined with NZM-XMC-TC-MB.		

Technical data

Environmental conditions

Operating temperature		°C	-10 - +50
Relative humidity, non-condensing (IEC/EN 60068-2-30)		%	5 - 95
Ambient temperature			
Storage	θ	°C	-10 - +50
Suitable for height			2000
Degree of Protection			IP20

Power supply module

Supply voltage	U _s		5 V DC
----------------	----------------	--	--------

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 6.0

PLC's (EG000024) / Fieldbus, decentr. periphery - communication module (EC001604)

Electric engineering, automation, process control engineering / Control / Field bus, decentralized peripheral / Field bus, decentralized peripheral - communications module (ec1@ss8.1-27-24-26-08 [BAA073010])

Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	0 - 0
Voltage type of supply voltage		DC
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for MODBUS		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for SERCOS		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		No
Radio standard Bluetooth		No
Radio standard WLAN 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
System accessory		Yes
Degree of protection (IP)		IP20
With potential separation		Yes
Fieldbus connection over separate bus coupler possible		No
Rail mounting possible		Yes
Wall mounting/direct mounting		No
Front build in possible		Yes
Rack-assembly possible		No
Suitable for safety functions		No
Category according to EN 954-1		-

SIL according to IEC 61508			None
Performance level acc. to EN ISO 13849-1			None
Appendant operation agent (Ex ia)			No
Appendant operation agent (Ex ib)			No
Explosion safety category for gas			None
Explosion safety category for dust			-
Width		mm	97
Height		mm	63
Depth		mm	97

Additional product information (links)

12/13 IL01219006Z (replaces AWA1230-2617)	
12/13 IL01219006Z (replaces AWA1230-2617)	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL01219006Z2013_12.pdf
05/13 MN01219001Z (replaces AWB1230-1630en)	
05/13 MN01219001Z (ersetzt AWB1230-1630de) - Deutsch	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN01219001Z_DE.pdf
05/13 MN01219001Z (replaces AWB1230-1630en) - English	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN01219001Z_EN.pdf