

Mounting kit, measuring module, XMC for 630A

Part no. **NZM-XMC-KIT-630**
 Article no. **153141**
 Catalog No. **NZM-XMC-KIT-630**



Delivery program

Product range		Accessories
Accessories		Measuring modules
Accessories		Accessories, diagnostics & communication
Description		<p>For applications with currents of up to 630 A</p> <p>Included as standard:</p> <ul style="list-style-type: none"> • Measuring module NZM3-XMC-MB • 3 pole terminal block • 3 cable lugs • Three stripped insulated 300 mm² conductors • 1 cover NZM3-XKSA
Number of poles		3 pole
For use with		NZM...3-AE(F)250...630(-NA), NZM...3-VE(F)250...630(-NA)
Rated operating frequency		AC 50/60 Hz
Standard/Approval		IEC
Construction size		NZM3
Notes		
Circuit-breakers not included as standard.		
The module can be set up using the Eaton Configurator (www.eaton.eu).		

Technical data

Max. current

Rated operational current	I_e	A AC	1 - 630
---------------------------	-------	------	---------

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9 Insulation properties		
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 6.0

PLC's (EG000024) / Fieldbus, decentr. periphery - communication module (EC001604)

Electric engineering, automation, process control engineering / Control / Field bus, decentralized peripheral / Field bus, decentralized peripheral - communications module (ec@ss8.1-27-24-26-08 [BAA073010])

Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	24 - 24
Voltage type of supply voltage		DC
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for MODBUS		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for SERCOS		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		No
Radio standard Bluetooth		No
Radio standard WLAN 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
System accessory		Yes
Degree of protection (IP)		IP20
With potential separation		Yes
Fieldbus connection over separate bus coupler possible		Yes
Rail mounting possible		No

Wall mounting/direct mounting			Yes
Front build in possible			No
Rack-assembly possible			No
Suitable for safety functions			No
Category according to EN 954-1			-
SIL according to IEC 61508			None
Performance level acc. to EN ISO 13849-1			None
Appendant operation agent (Ex ia)			No
Appendant operation agent (Ex ib)			No
Explosion safety category for gas			None
Explosion safety category for dust			None
Width		mm	209
Height		mm	132
Depth		mm	91

Additional product information (links)

12/13 IL01219006Z (replaces AWA1230-2617)	
12/13 IL01219006Z (replaces AWA1230-2617)	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL01219006Z2013_12.pdf
05/13 MN01219001Z (replaces AWB1230-1630en)	
05/13 MN01219001Z (ersetzt AWB1230-1630de) - Deutsch	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN01219001Z_DE.pdf
05/13 MN01219001Z (replaces AWB1230-1630en) - English	ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN01219001Z_EN.pdf