



## Set of clamp-type terminals f. GST1, 70-150mm<sup>2</sup>

**Part no.**                    **PSK1**  
**Article no.**                **038734**



Powering Business Worldwide™

### Delivery program

Product range		60 mm system
Subrange		Sets of clamp-type terminals
Information about equipment supplied		One set comprises 3 clamp-type terminals
Clamping range		1 x (70 - 150) mm <sup>2</sup> Cu/Al
For use with		GSU1, GST...1

### Technical data

#### Electrical

Direction of incoming supply		as required
------------------------------	--	-------------

#### Mechanical

Climatic proofing		Damp heat, constant, to IEC 60068--2--3 Damp heat, cyclical, to IEC 60068--2--30
Mounting position		Vertical or horizontal

### Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)			
Electric engineering, automation, process control engineering / Electrical installation, device / Clamp (not overhead line) / Switch board (ecl@ss8.1-27-14-11-46 [BAA025010])			
Busbar thickness		mm	0 - 0
Busbar width		mm	60 - 60
Suitable for			-
Width clamp		mm	0
Max. conductor cross section		mm <sup>2</sup>	150
Max. rated operation current I <sub>e</sub>		A	0
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			No
Suitable for strip conductor connection			No