Power incoming cable, flat cable, L=1.5m

Part no. RA-C3/C1-1,5HF
Article no. 290210
Catalog No. RA-C3-C1-1P5HF

Delivery program

Product range			Power supply at flat cable RA-C1
Subrange			Power connection cable
Basic function			for connecting the device with the 400 V AC flexible busbar junction
Description			with power plug and plug for flexible busbar junction, halogen-free, 5 x 1.5 mm^2
For use with			
For use with			RAMO RASP RA-C1-PLF
Length		m	1.5

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	0

Technical data ETIM 6.0

Batteries, chargers, power cords (EG000053) / Power cord (EC001576)			
Electric engineering, automation, process control engineering / Cable, wire / Ready-made low-voltage line / Extension line (low-voltage line) (ecl@ss8.1-27-06-04-02 [AAB665010])			
Connection 1			-
Connection 2			-
Connector system system-oriented			Yes
Number of cores			5
Nominal cross section conductor		mm^2	1.5
Length		m	1.5
Material outer sheath			-
Temperature resistance		°C	0 - 0
Nominal voltage		V	500
Colour outer sheath			Grey
Spiralized cable			No
Protective conductor			Yes
Oil resistant (acc. EN 60811-404)			Yes
With cord switch			No
Outer diameter approx.		mm	10

Additional product information (links)

AWA2190-1936 Rapid Link: Speed Control Unit	
AWA2190-1936 Rapid Link: Speed Control Unit	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/19360110.pdf
AWA2190-2058 Rapid Link: Motor Control Unit	
AWA2190-2058 Rapid Link: Motor Control Unit	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/20580809.pdf
CA04020001Z-DE Sortimentskatalog: Antriebstechnik effizient gestalten, Motoren starten und steuern	http://www.eaton.eu/DE/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_1095238_de.pdf

© 11/2016 by Eaton Industries GmbH