



Motor cable, 10m, halogen free, for RAMO

Part no. RAMO-CM1-10M
Article no. 164284
Catalog No. RAMO-CM1-10M

Delivery program

Product range			Motor feeder
Subrange			Motor cable
Basic function			for connecting the motor starter to the motor
Description			halogen free, 8 x 1.5 mm ² , plastic plug
For use with			
For use with			RAMO
Length		m	10

Technical data

General

Standards			EN 61684 DIN VDE 0110
Degree of Protection			IP65 IEC/EN 60529
Ambient temperature			
Operation	ø	°C	-30 - +70

Connection cable

Terminal capacities		mm ²	8 x 1.5
Outer cable diameter		mm	9 - 13
Minimum bending radius		mm	6 x outer cable diameter
Material			Outer casing halogen free Cable: Cu flexible to VDE 0295 Class 5
Colour			Silver grey (RAL 7001)
Resistance to oils and acids			VDE 0472 Part 803 B
Flame retardance, fire propagation			EN 50265-2-1

Metal housing with plug-in connection

Conductor cross-section		mm ²	Contact pins: 8 x 1.5
Material			
Contacts			Polycarbonate
Contact material			Silver-plated copper
Housing			Polycarbonate
Locking facility			Polyamide

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-30
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Accessories for frequency controller (EC002025)			
Electric engineering, automation, process control engineering / Electrical drive / Electrical drive (accessories) / Frequency controller (accessories) (ecI@ss8.1-27-02-92-01 [ACN127008])			
Type of accessory			-

Additional product information (links)

CA04020001Z-DE Sortimentskatalog: Antriebstechnik effizient gestalten, Motoren starten und steuern	http://www.eaton.eu/DE/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_1095238_de.pdf
--	---