



Motor cable, 2m, halogen free, for RASP

Part no. RASP-CM1-2M0
Article no. 164285
Catalog No. RASP-CM1-2M0

Delivery program

Product range			Motor feeder
Subrange			Motor cable
Basic function			for connecting the motor starter to the motor
Description			halogen free, screened, 4 x 1.5 mm ² + 2 x (2 x 0.75 mm ²), plastic plug
For use with			
For use with			RASP
Length		m	2

Technical data

General

Standards			EN 61684 DIN VDE 0110
Degree of Protection			IP65 IEC/EN 60529
Ambient temperature			
Operation	ø	°C	-30 - +70

Connection cable

Terminal capacities		mm ²	4 x 1.5 + 2 x (2 x 0.75) screened
Outer cable diameter		mm	9 - 13
Minimum bending radius		mm	10 x outer cable diameter
Material			Outer casing halogen free Cable: Cu flexible to VDE 0295 Class 6
Colour			Orange (RAL 2003)
Resistance to oils and acids			VDE 0472 Part 803 A/B
Flame retardance, fire propagation			IEC 60332-2

Metal housing with plug-in connection

Conductor cross-section		mm ²	Contact pins: 4 x 1.5 + 4 x 0.75
Material			
Contacts			Polycarbonate
Contact material			Silver-plated copper
Housing			Polycarbonate
Locking facility			Polyamide

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-30
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Accessories for frequency controller (EC002025)			
Electric engineering, automation, process control engineering / Electrical drive / Electrical drive (accessories) / Frequency controller (accessories) (ecI@ss8.1-27-02-92-01 [ACN127008])			
Type of accessory			-

Additional product information (links)

CA04020001Z-DE Sortimentskatalog: Antriebstechnik effizient gestalten, Motoren starten und steuern	http://www.eaton.eu/DE/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_1095238_de.pdf
--	---