



Filament lamp, 130 V, BA15d, 5-7W

Part no. SL-L130
 Article no. 205349
 Catalog No. SL-L130

Delivery program

Product range			SL signal towers
Single unit/Complete unit			Stand-alone device
			Socket size BA-15d Power 5 - 7 W
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	t_{mean} (AC)	h	5000
Rated operational voltage	U_e	V	110 ... 130 V
Connection to SmartWire-DT			no

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 6.0

Lamps (EG000028) / Indication- and signalling lamp (EC000399)			
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss8.1-27-11-06-31 [AKE242011])			
Lamp voltage		V	130 - 130
Luminous flux		lm	0
Socket			BA15d
Lamp type			Incandescent lamp
Lamp shape			Pear-shape
Halogen			No
Krypton			No
Xenon			No
Colour			None
Colour temperature		K	2800
Diameter		mm	0
Total length		mm	0
Suitable for torches			No
Suitable for pointer			Yes
Nominal current		mA	46
Lamp power		W	6
Average nominal lifespan		h	3000

Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			012528
CSA Class No.			3211-03
North America Certification			UL listed, CSA certified

Additional product information (links)

IL04716024Z (AWA1160-1685) Pillar lamps	
IL04716024Z (AWA1160-1685) Pillar lamps	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2011_02.pdf