


**LED, green, BA15d, 230 V**

**Part no. SL-LED230-G**  
**Article no. 285534**  
**Catalog No. SL-LED230-G**



## Delivery program

Product range			SL signal towers
Single unit/Complete unit			Stand-alone device
			Socket size BA-15d
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	$t_{\text{mean}}$ (AC)	h	100000
Rated operational voltage	$U_e$	V	110 - 230 V AC 50/60 Hz
Rated operational current	$I_e$	mA	9 - 17
<b>Colour</b>			Green
			
Connection to SmartWire-DT			no

## Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

## Technical data ETIM 6.0

Lamps (EG000028) / Indication- and signalling lamp (EC000399)			
Electric engineering, automation, process control engineering / Lighting installation, device / Light medium / Indication- and signal lamp (ecl@ss8.1-27-11-06-31 [AKE242011])			
Lamp voltage		V	230 - 230
Luminous flux		lm	0
Socket			BA15d
Lamp type			LED
Lamp shape			-
Halogen			No
Krypton			No
Xenon			No
Colour			Green
Colour temperature		K	0
Diameter		mm	0
Total length		mm	42
Suitable for torches			No
Suitable for pointer			Yes
Nominal current		mA	17
Lamp power		W	3,5
Average nominal lifespan		h	100000

## Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			012528
CSA Class No.			3211-03
North America Certification			UL listed, CSA certified

## Additional product information (links)

<b>IL04716024Z (AWA1160-1685) Pillar lamps</b>	
IL04716024Z (AWA1160-1685) Pillar lamps	<a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2011_02.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2011_02.pdf</a>