



Touch panel, ir, 24 V DC, 10.4z, TFTcolor, ethernet, RS232, profibus, (PLC)



Powering Business Worldwide™

Part no. **XVS-440-10MPI-1-10**
 Article no. **139973**

Delivery program

| | | | |
|---|--|-------|---|
| Product range | | | XVS400 10.4" |
| Product range | | | XVS400 |
| Function | | | HMI-PLC (PLC retrofitted by user) |
| Common features of the model series | | | Ethernet interface USB device RS232 Profibus/MPI UL508, cUL approvals PLC function can be fitted by user Communications scope can be fitted by user with licenses |
| Display - Type | | | Color display, TFT |
| Touch-technology | | | Infra-red touch |
| Number of colours | | | Adjustable: 65536 or 256 colours |
| Resolution | | Pixel | VGA 640 x 480 |
| Portrait format | | | yes |
| Screen diagonal | | Inch | 10.4 |
| Model | | | Metal enclosure and front plate |
| Operating system | | | Windows CE (license required) CompactFlash card required |
| PLC-licence | | | Can be fitted by user with article no. 140390 LIC-PLC-MXP-MEDIUM |
| License certificates for onboard interfaces | | | Can be expanded as required, see Accessories -> License product certificates |
| built-in interfaces | | | 1 x Ethernet 100base-TX/10base-T 1 x RS232 1 x PROFIBUS/MPI 2 x USB host 1 x USB device |
| Front type | | | Standard front with standard membrane Laminated safety glass, non-reflective |
| Utilization | | | Flush mounting |
| Slots | | | for Compact-Flash™ Cards: 2 |
| Memory card automation | | | required, see Accessories -> Memory cards |
| Pluggable communication cards (optional) | | | no |
| Heat dissipation | | W | 24 |

Technical data

Display

| | | | |
|-----------------------------------|--|-------------------|--|
| Display - Type | | | Color display, TFT |
| Screen diagonal | | Inch | 10.4 |
| Resolution | | Pixel | VGA 640 x 480 |
| Visible screen area | | mm | 211 x 158 |
| Number of colours | | | Adjustable: 65536 or 256 colours |
| Contrast ratio (Normally) | | | Normally 350:1 |
| Brightness | | cd/m ² | Normally 350 |
| Back-lighting | | | 2 x CCFL dimmable via software |
| Service life of back-lighting | | h | Normally 50000 |
| Infra-red touch protective screen | | | Laminated safety glass, non-reflective |

Operation

| | | | |
|------------|--|--|---|
| Technology | | | Infra-red touch 79 x 59 logic channels |
|------------|--|--|---|

System

| | | | |
|-----------------|--|--|---|
| Internal memory | | | DRAM (OS, Program and data memory): 64 MByte Flash (can be used for data backup): approx. 1.5 MByte available NVRAM (retained data): approx. 32 KByte available |
| External memory | | | CF-Slot: 2 x CompactFlash Card type I/II for operating system, programs and data |

| | | | |
|-------------------------------|--|--|---|
| Back-up of real-time clock | | | |
| Battery (service life) | | | Zero maintenance |
| Backup (time at zero voltage) | | | Normally 10 years |
| Operating system | | | Windows CE (license required) CompactFlash card required |

Engineering

| | | | |
|--------------------------|--|--|---|
| Visualisation software | | | GALILEO EPAM XSOFT-CODESYS-2 XSOFT-CODESYS-3 |
| PLC-Programming software | | | XSOFT-CODESYS-2 XSOFT-CODESYS-3 |

Interfaces, communication

| | | | |
|---------------------|--|--|---|
| built-in interfaces | | | 1 x Ethernet 100base-TX/10base-T 1 x RS232 1 x PROFIBUS/MPI 2 x USB host 1 x USB device |
| PLC-licence | | | Can be fitted by user with article no. 140390 LIC-PLC-MXP-MEDIUM |
| USB Host | | | 2 x USB 2.0 (1.5 - 12 Mbit/s), not galvanically isolated |
| USB device | | | USB 1.1, not galvanically isolated |
| RS-232 | | | RS-232, not galvanically isolated (SUB-D plug 9 pole, UNC) |
| CAN | | | CAN, galvanically isolated (SUB-D plug 9 pole, UNC) |
| Slots | | | for Compact-Flash TM Cards: 2 |
| Ethernet | | | 100Base-TX/10Base-T |

Power supply

| | | | |
|--------------------------|-------------------|----|---|
| Nominal voltage | | | 24 V DC SELV (safety extra low voltage) |
| permissible voltage | | | Effective: 20.4-28.8 V DC (rated operating voltage -15%/+20%) Absolute with ripple: 19.2-30.0 V DC 35 V DC for a duration of < 100 ms |
| Voltage dips | | ms | ≤ 10 ms from rated voltage (24 V DC) 5 ms from undervoltage (20.4 V DC) |
| Power consumption | P _{max.} | W | 24 |
| Power consumption | | W | Normally 14 |
| Heat dissipation | | W | 24 |
| Note on heat dissipation | | | Heat dissipation with power consumption for 24 V 18 W for basic device + two times 3 W for USB modules |
| Siemens MPI, (optional) | | | yes |
| Type of fuse | | | Yes (fuse not accessible) |
| Potential isolation | | | no potential isolation (0 V-connection to housing potential) |

General

| | | | |
|---|--|----|---|
| Housing material | | | Metal, anodized |
| Front type | | | Standard front with standard membrane Laminated safety glass, non-reflective |
| Weight | | kg | 3.7 |
| Degree of protection (IEC/EN 60529, EN50178, VBG 4) | | | IP65 (at front), IP20 (at rear) |
| Approvals | | | |
| Approvals | | | cUL (UL508) |
| Applied standards and directives | | | |
| EMC | | | (in relation to CE) EN 61000-6-2 EN 61000-6-3 EN 61000-6-4 EN 61131-2 |
| Product standards | | | EN 50178 EN 61131-2 |
| Security | | | EN 60950 UL 60950 |
| Mechanical shock resistance | | g | according to IEC 60068-2-27 |
| Vibration | | | To IEC 68-2-6 |

Environmental conditions

| | | | |
|---------------------|---|----|-----------|
| Temperature | | | |
| Operation | θ | °C | 0 - +50 |
| Storage / Transport | θ | °C | -20 - +60 |

| | | |
|------------------------------------|----|--------------------------|
| Operating ambient temperature min. | °C | 0 |
| Operating ambient temperature max. | °C | + 50 |
| Relative humidity | | |
| Relative humidity | | 10 - 95%, non-condensing |

Supply voltage U_{Aux}

| | | | |
|--------------------------------------|-----------|---|--------------------|
| Rated operational voltage | U_{Aux} | V | 24 V DC (-15/+20%) |
| Protection against polarity reversal | | | Yes |
| Potential isolation | | | No |

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|------------|----|--|
| Rated operational current for specified heat dissipation | I_n | A | 0 |
| Heat dissipation per pole, current-dependent | P_{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P_{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P_{vs} | W | 24 |
| Heat dissipation capacity | P_{diss} | W | 0 |
| Operating ambient temperature min. | | °C | 0 |
| Operating ambient temperature max. | | °C | 50 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Please enquire |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Meets the product standard's requirements. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 6.0

| | | | |
|---|--|---|-------------|
| PLC's (EG000024) / Graphic panel (EC001412) | | | |
| Electric engineering, automation, process control engineering / Control / Operate and Observe (HMI) / Graphic panel (HMI) (ecl@ss8.1-27-24-23-02 [BAA722010]) | | | |
| Supply voltage AC 50 Hz | | V | 0 - 0 |
| Supply voltage AC 60 Hz | | V | 0 - 0 |
| Supply voltage DC | | V | 20.4 - 28.8 |
| Voltage type of supply voltage | | | DC |
| Number of HW-interfaces industrial Ethernet | | | 1 |
| Number of HW-interfaces PROFINET | | | 0 |
| Number of HW-interfaces RS-232 | | | 1 |

| | | |
|---|-------|-------|
| Number of HW-interfaces RS-422 | | 0 |
| Number of HW-interfaces RS-485 | | 0 |
| Number of HW-interfaces serial TTY | | 0 |
| Number of HW-interfaces USB | | 2 |
| Number of HW-interfaces parallel | | 0 |
| Number of HW-interfaces Wireless | | 0 |
| Number of HW-interfaces other | | 0 |
| With SW interfaces | | Yes |
| Supporting protocol for TCP/IP | | Yes |
| Supporting protocol for PROFIBUS | | Yes |
| Supporting protocol for CAN | | No |
| Supporting protocol for INTERBUS | | No |
| Supporting protocol for ASI | | No |
| Supporting protocol for KNX | | No |
| Supporting protocol for MODBUS | | Yes |
| Supporting protocol for Data-Highway | | No |
| Supporting protocol for DeviceNet | | No |
| Supporting protocol for SUCONET | | No |
| Supporting protocol for LON | | No |
| Supporting protocol for PROFINET IO | | No |
| Supporting protocol for PROFINET CBA | | No |
| Supporting protocol for SERCOS | | No |
| Supporting protocol for Foundation Fieldbus | | No |
| Supporting protocol for EtherNet/IP | | Yes |
| Supporting protocol for AS-Interface Safety at Work | | No |
| Supporting protocol for DeviceNet Safety | | No |
| Supporting protocol for INTERBUS-Safety | | No |
| Supporting protocol for PROFIsafe | | No |
| Supporting protocol for SafetyBUS p | | No |
| Supporting protocol for other bus systems | | Yes |
| Radio standard Bluetooth | | No |
| Radio standard WLAN 802.11 | | No |
| Radio standard GPRS | | No |
| Radio standard GSM | | No |
| Radio standard UMTS | | No |
| IO link master | | No |
| Type of display | | TFT |
| With colour display | | Yes |
| Number of colours of the display | | 65536 |
| Number of grey-scales/blue-scales of display | | 0 |
| Screen diagonal | inch | 10.4 |
| Number of pixels, horizontal | | 640 |
| Number of pixels, vertical | | 480 |
| Useful project memory/user memory | kByte | 64000 |
| With numeric keyboard | | Yes |
| With alpha numeric keyboard | | Yes |
| Number of function buttons, programmable | | 0 |
| Number of buttons with LED | | 0 |
| Number of system buttons | | 1 |
| With touch screen | | Yes |
| With message indication | | Yes |
| With message system (incl. buffer and confirmation) | | Yes |
| Process value representation (output) possible | | Yes |
| Process default value (input) possible | | Yes |
| With recipes | | Yes |

| | | |
|--|----|--------|
| Number of password levels | | 200 |
| Printer output available | | Yes |
| Number of online languages | | 100 |
| Additional software components, loadable | | Yes |
| Degree of protection (IP), front side | | IP65 |
| Operation temperature | °C | 0 - 50 |
| Rail mounting possible | | No |
| Wall mounting/direct mounting | | No |
| Suitable for safety functions | | No |
| Width of the front | mm | 345 |
| Height of the front | mm | 260 |
| Built-in depth | mm | 62 |

Approvals

| | | |
|--------------------------------------|--|---|
| Product Standards | | UL 60950-01; CSA-C22.2 No. 60950-1; IEC/EN 61131-2; CE marking |
| UL File No. | | E208621 |
| UL Category Control No. | | NWGQ2, NWGQ8 |
| CSA File No. | | UL report applies to both US and Canada |
| CSA Class No. | | - |
| North America Certification | | UL recognized, certified by UL for use in Canada |
| Conditions of Acceptability | | The investigated Pollution Degree is: 2 Proper bonding to the end-product main protective earthing termination is: Required The following end-product enclosures are required: Fire, Electrical The unit must be supplied via a SELV source. The provided Ethernet Connection is only allowed to connect to inhouse networks. |
| Specially designed for North America | | No |
| Current Limiting Circuit-Breaker | | No |
| Degree of Protection | | IEC: IP65, UL/CSA Type: - |

Dimensions

Dimensions

Additional product information (links)

IL04802011Z Enclosed kit information

IL04802011Z Enclosed kit information ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04802011Z2013_03.pdf

MN04802012Z Operator manual XVS400 10.4"/12.1"/15"

MN04802012Z Betriebsanleitung XVS400 10,4"/12,1"/15" - Deutsch ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802012Z_DE.pdf

MN04802012Z Operator manual XVS400 10.4"/12.1"/15" - English ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802012Z_EN.pdf

MN04802093Z XSoft-CoDeSys-2, PLC programming XVS400

MN04802093Z XSoft-CoDeSys-2, SPS-Programmierung XVS400 - Deutsch ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802094Z-DE.pdf

MN04802093Z XSoft-CoDeSys-2, SPS-Programmierung XVS400 - Deutsch ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802094Z_DE.pdf

MN04802093Z XSoft-CoDeSys-2, PLC programming XVS400 - English ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802094Z-EN.pdf

MN04802093Z XSoft-CoDeSys-2, PLC programming XVS400 - English ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN04802094Z_EN.pdf

MN048008ZU Manual XSOFT-CODESYS-3, PLC programming

MN048008ZU Handbuch XSOFT-CODESYS-3, SPS-Programmierung - Deutsch ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN048008ZU_DE.pdf

MN048008ZU Manual XSOFT-CODESYS-3, PLC programming - English ftp://ftp.moeller.net/DOCUMENTATION/AWB_MANUALS/MN048008ZU_EN.pdf