



**Distribution cabinet, HxWxD=2000x1200x600mm, IP40**

**Part no.                   XVTL-BF-12/6/20**  
**Article no.               114438**

**Design verification as per IEC/EN 61439**

| Technical data for design verification   |                |    |  |
|--|----------------|----|--|
| Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees, calculated as per IEC 60890                  |                |    |  |
| Individual enclosure, free-standing  | P <sub>V</sub> | CO | 373  |
| Starting enclosure, free-standing  | P <sub>V</sub> | CO | 360  |
| Middle enclosure, free-standing  | P <sub>V</sub> | CO | 348  |
| Individual enclosure for wall mounting   | P <sub>V</sub> | CO | 349  |
| Starting enclosure for wall mounting   | P <sub>V</sub> | CO | 341  |
| Middle enclosure for wall mounting   | P <sub>V</sub> | CO | 337  |
| Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees, calculated as per IEC 60890                  |                |    |  |
| Individual enclosure, free-standing  | P <sub>V</sub> | CO | 747  |
| Starting enclosure, free-standing  | P <sub>V</sub> | CO | 721  |
| Middle enclosure, free-standing  | P <sub>V</sub> | CO | 698  |
| Individual enclosure for wall mounting   | P <sub>V</sub> | CO | 699  |
| Starting enclosure for wall mounting   | P <sub>V</sub> | CO | 684  |
| Middle enclosure for wall mounting   | P <sub>V</sub> | CO | 675  |
| IEC/EN 61439 design verification   |                |    |  |
| 10.2 Strength of materials and parts   |                |    |  |
| 10.2.2 Corrosion resistance  |                |    | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures   |                |    | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |                |    | Not applicable.  |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                |    | Not applicable.  |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |                |    | Not relevant to indoor installations.  |
| 10.2.5 Lifting   |                |    | Met; assembled and secured as per the latest applicable instruction leaflet.   |
| 10.2.6 Mechanical impact   |                |    | IK10   |
| 10.2.7 Inscriptions  |                |    | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |                |    | IP40   |
| 10.4 Clearances and creepage distances   |                |    | Is the panel builder's responsibility.   |
| 10.5 Protection against electric shock   |                |    | < 0.1 Ω; meets the product standard's requirements.  |
| 10.6 Incorporation of switching devices and components   |                |    | Is the panel builder's responsibility.   |
| 10.7 Internal electrical circuits and connections  |                |    | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |                |    | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |                |    |  |
| 10.9.2 Power-frequency electric strength   |                |    | U <sub>i</sub> = 690 V AC  |
| 10.9.3 Impulse withstand voltage   |                |    | 6 kV   |
| 10.9.4 Testing of enclosures made of insulating material   |                |    | Does not apply to metal enclosures.  |
| 10.10 Temperature rise   |                |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |                |    | Is the panel builder's responsibility.   |
| 10.12 Electromagnetic compatibility  |                |    | Is the panel builder's responsibility.   |
| 10.13 Mechanical function  |                |    | Meets the product standard's requirements.   |

## Technical data ETIM 6.0

|   |    |                     |
|---|----|---------------------|
| Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)   |    |                     |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss8.1-27-18-01-01 [AGZ056013]) |    |                     |
| Width   | mm | 1200                |
| Height  | mm | 2000                |
| Depth   | mm | 608.5               |
| Material  |    | Steel               |
| Type of surface   |    | With powder coating |
| Colour  |    | Grey                |
| RAL-number  |    | 7035                |
| With mounting plate   |    | No                  |
| Mounting plate depth-adjustable   |    | Yes                 |
| Number of locks   |    | 1                   |
| Floor installation possible   |    | Yes                 |
| Wall fastening possible   |    | Yes                 |
| Wall build in   |    | No                  |
| Pole fastening  |    | No                  |
| Tackable  |    | Yes                 |
| Number of doors   |    | 2                   |
| Suitable for metrical mounting  |    | Yes                 |
| Suitable for outdoor set-up   |    | No                  |
| Pitched roof  |    | No                  |
| EMC-version   |    | Yes                 |
| Impact strength   |    | IK10                |
| Degree of protection (IP)   |    | IP40                |
| With glazed door  |    | No                  |
| With ventilation door   |    | No                  |
| With backside door  |    | No                  |