

Door, glass, right, for HxW=1800x1200mm

Part no. **XVTL-DG-12-18-R**

Article no. **114668**



Delivery program

Product range			Control centres XVTL
Basic function			Combination enclosures
Product function			Accessories
Accessories			Doors
Single unit/Complete unit			Modular system
Description			Transparent doors Single wing door 3-point turn lock with roller lever lock Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249)
Material			Sheet steel 1.25 mm
Surface finish			Polyester powder coating RAL 7035, light grey RAL 9016, traffic white
Information about equipment supplied			can be used as right door for two-leaf versions order left and right door leaf separately Including screws
Protection type			IP55
Suitable for width			1200
Suitable for height			1800
			Protective cover mounted on right

Technical data ETIM 6.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss8.1-27-18-22-04 [ACN614008])			
Model			Protective door
Version as glazed door			Yes
Version as door for disconnecting switch interlocking			No
Width		mm	593
Height		mm	1740
Depth		mm	40
EMC-version			Yes
Material			Steel
Type of surface			With powder coating
Colour			Grey
Degree of protection (IP)			IP55