



## Distribution cabinet, HxWxD=1800x600x400mm, IP55

**Part no.** XVTL-MP/BX/IC-6/4/18  
**Article no.** 114565

### Delivery program

Product range			Control centres XVTL
Basic function			Combination enclosures
Single unit/Complete unit			Complete housing
Degree of Protection			IP55 (with door and flange)
Description			Fragment basic equipment Including open cable entries top, prepared for F3A flange
Material			Sheet steel 2 mm
Surface finish			Polyester powder coating Phosphated RAL 7035, light grey
Colour			light gray (RAL 7035)
Information about equipment supplied			including frame, sheet steel doors, back plate, bottom and top plate, mounting plate, lifting eyelets, cylinder lock and branding strip Including support frame for the IVS mounting units including insulating surround and mounted insulated support bracket Without side walls
Width		mm	600
Height		mm	1800
Depth		mm	400

### Technical data

#### General

Standards			IEC/EN 60439-1 IEC/EN 60439-3 IEC/EN 62208
Protection class			1
			40 °C (intermittent maximum value) 35 °C (maximum value, 24 h average) -5 °C (minimum value)
Installation conditions			Indoor installation
Degree of Protection			IP55 (with door and flange)
Relative humidity			50% (at 40°C)
Power loss			
Max. admissible heat dissipation, ambient air temperature +35 °C		W	386
Weight		kg	80

#### Material characteristics

Material			Sheet steel 2 mm
Surface treatment			Painting, phosphated and polyester powder coating
Surface finish			Polyester powder coating Phosphated RAL 7035, light grey
Colour			light gray (RAL 7035)
Material characteristics			
Type Door			Outside-supported doors with hidden hinges Can be removed from 90°
door opening angle			120° (single mounting) 120° (combination mounting)
Door interlock			Folding handle with espagnolette lock Can be fitted with profile cylinder Three-point interlock

#### Material properties

Mechanical			
Cable entry			Various covers allow cable entry from above and/or below

Electrical			
Rated insulation voltage	U <sub>i</sub>	V	690
Rated operational voltage	U <sub>e</sub>	V	415
Rated frequency	f	Hz	50 (AC)
Rated impulse withstand voltage	U <sub>imp</sub>	kV	6
Rated operational current	I <sub>e</sub>	A	2500
Overvoltage category/pollution degree			IV/3
Rated short-time withstand current (t=1s)	I <sub>cw</sub>	kA	65
Rated peak withstand current	I <sub>pk</sub>	kA	143
Max. admissible heat dissipation, ambient air temperature +35 °C		W	386
Earthings			Screw M10: 50 × 106 A <sup>2</sup> s (base frame, main earthing) Taptite screw M6: 3.9 × 106 A <sup>2</sup> s (enclosure side plate, back plate) M6 weld stud: 50 × 106 A <sup>2</sup> s (door)

## Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees, calculated as per IEC 60890			
Individual enclosure, free-standing	P <sub>V</sub>	CO	185
Starting enclosure, free-standing	P <sub>V</sub>	CO	172
Middle enclosure, free-standing	P <sub>V</sub>	CO	152
Individual enclosure for wall mounting	P <sub>V</sub>	CO	163
Starting enclosure for wall mounting	P <sub>V</sub>	CO	145
Middle enclosure for wall mounting	P <sub>V</sub>	CO	132
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees, calculated as per IEC 60890			
Individual enclosure, free-standing	P <sub>V</sub>	CO	370
Starting enclosure, free-standing	P <sub>V</sub>	CO	346
Middle enclosure, free-standing	P <sub>V</sub>	CO	304
Individual enclosure for wall mounting	P <sub>V</sub>	CO	326
Starting enclosure for wall mounting	P <sub>V</sub>	CO	291
Middle enclosure for wall mounting	P <sub>V</sub>	CO	265
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Not applicable.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Not applicable.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Met; assembled and secured as per the latest applicable instruction leaflet.
10.2.6 Mechanical impact			IK10
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			IP55
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			U <sub>i</sub> = 690 V AC
10.9.3 Impulse withstand voltage			6 kV
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.

10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		Meets the product standard's requirements.

## Technical data ETIM 6.0

Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)		
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss8.1-27-18-01-01 [AGZ056013])		
Width	mm	600
Height	mm	1800
Depth	mm	400
Material		Steel
Type of surface		With powder coating
Colour		Grey
RAL-number		7035
With mounting plate		Yes
Mounting plate depth-adjustable		No
Number of locks		1
Floor installation possible		Yes
Wall fastening possible		Yes
Wall build in		No
Pole fastening		No
Tackable		Yes
Number of doors		1
Suitable for metrical mounting		Yes
Suitable for outdoor set-up		No
Pitched roof		No
EMC-version		Yes
Impact strength		IK10
Degree of protection (IP)		-
With glazed door		No
With ventilation door		No
With backside door		No